

Tunstall Air Valves

Established 1958

About Tunstall Air Valves (Steam)

- Tunstall steam air valves are made, assembled, tested, and inspected in the U.S.
- Each unit is individually packaged with external labeling for inventory convenience and maintenance.
- Steam valves have brass internals, with nickel plated and hand polished exterior.
- 1P vents have a wide adjustment range, which simplifies the balancing of heat to each radiator.

Steam Valves



Quick, uniform distribution of heat to all radiation is essential to one pipe steam performance. This requires balancing the radiation by controlled venting. Tunstall's #1P air valves are adjustable and all steam air valves are designed for positive action and straightline venting. They function automatically to vent the air.

TUNSTALL STEAM VENTS							
USE FOR	NO.	CONNECTION	PORT	MAX OPER. PRES.	OVERALL HEIGHT		
FREE STANDING RADIATORS	1P	1/8" ADJUSTABLE	3/32"	3 PSI	3 1/4"		
	11P	1/8" MALE	1/16"	6 PSI	2 3/4"		
CONVECTOR AND RISERS	31P	1/8" MALE	1/16"	6 PSI	3 3/4"		
	33P	1/4" MALE	1/16"	6 PSI	3 3/4"		
MAIN VENTO	35P	3/4" MALE x 1/2" FEMALE	3/32"	3 PSI	3 1/4"		
MAIN VENTS	75P		3/32"	5 PSI	4 5/8"		

NOTES:

- 1. Maximum operating pressure or drop away pressure is the maximum pressure at which the vent will continue to open and close by gravity.
- 2. One pipe steam systems function best when pressure is less than 2 psi.
- 3. The lower the pressure at which a system is operated, the greater its efficiency will be.

Tunstall Air Valves

TUNSTALL HOT WATER VENTS						
USE FOR	NO.	CONNECTION	MAX OPER. PRES.			
RADIATORS	9P	1/8" MALE	150 PSI			
RADIATORS	10P	1/8" MALE	150 PSI			
AS REQUIRED	700P	1/8" MALE	50 PSI			
AS REQUIRED	14, 14A	1/8" MALE	150 PSI			







10P







TUNSTALL # DOLE #		Connection Size/Description	Steam (S) or Hot Water (HW)	
1P	1P 1A 1/8" M Angle, Adjustable		S	
9P	9	1/8" M Coin Valve	HW	
10P	10	1/8" M Key Valve	HW	
10-4P	10-4	KEY for #10	HW	
11P	1933	1/8" M Angle	S	
31P	1933	1/8" M Straight	S	
33P	1933	1/4" M Straight	S	
35P	1933	3/4" M x 1/2" F Straight	S	
75P	3C	3/4" x 1/2" Vent for Mains	S	
700P	2000	1/8" M Straight, Hydronic Float Vent	HW	
14	14	1/8" M Key Air Valve Assembly, 20" x 3/16" Tubing	HW	
14A	14A	1/8" M Coin Air Valve Assembly, 20" x 3/16" Tubing	HW	

Distributed By: